

WORKTOP OIL



Ciranova WORKTOP OIL is the perfect finish for wooden worktops, cutting boards, furniture, and tables on which food is prepared. The WORKTOP OIL provides natural, water-repellent protection. Ciranova WORKTOP OIL has been tested in line with the 1935/2004 standard and, after drying, meets the requirements to be used on wood that comes into contact with food. Ciranova WORKTOP OIL is made from natural waxes, modified oils, and vegetable and renewable fatty acids.

- » Very suitable for wooden worktops, cutting boards, and tables.
- » Provides a water and stain-resistant finish.
- » Tested according to the NO 1935/2004 article 3C standard.
- » Easy to apply."

TECHNICAL DATA

Type of product

solventborn

Cleaning

Ciranova cleaning thinner

Gloss level

Mat & Satin

Viscosity

+/- 50 sec - DIN 4mm

Solid substances

+/- 46%

Outer packaging

12 x 500ml

Coverage

30-35 m²/liter per coat

Drying times

Paintable: after +/- 6 hours

Fully cured after +/- 7 days

Sanding grit

P 120-150

Storage/transport

between 5°C and 25°C

Shelf life

48 months in original and unopened packaging.

Disposal

Dispose of residues and empty packaging in accordance with local regulations.

Ciranova® products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However they are drawn to our best knowledge and ability, the user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.



500 ml



PROTECTION
INDOOR

PREPARATION

Ensure that all old finishing layers have been completely removed and that the surface is free of dust and other contaminants.

APPLICATION

Shake the WORKTOP OIL well before use. You can easily apply the Ciranova WORKTOP OIL with a lint-free cloth in the direction of the wood grain. For larger surfaces, you can use a brush.

Apply a thin layer and let the oil soak into the wood for 15 minutes, then wipe the surface dry with a lint-free cloth. For hard woods such as oak, at least 2 coats are required. Multiple coats can be used for soft woods.

DRYING TIME

Can be painted over after +/- 6 hours. Drying times depend on the amount applied, ambient temperature, humidity, and ventilation.

FINISHING

Use Ciranova WORKTOP OIL as both a base and final coat.

MAINTENANCE

Apply a new coat of WORKTOP OIL Ciranova regularly to ensure permanent water-repellent protection. In the event of heavy soiling, use the Ciranova intensive cleaner to clean the wood first. WORKTOP OIL is only fully cured after +/- 7 days. Do not treat with water or maintenance products.

IMPORTANT INFORMATION ⚠

Dried oil residues are self-combustible. Used pads and cloths should be immersed in water after use.