

# Lagoon™



Cleans and preserves the original finish of the floor without smears



No need to rinse



Suitable on oiled and lacquered wood floors



Also suitable on melamine, PVC and laminated floors



Ideal for frequent cleaning



Slip resistant



## PRODUCT DESCRIPTION

- Blanchon **Lagoon™** allows you to clean most wooden floors, especially lacquered and oiled ones, whether prefinished or finished on site, floated or glued down, etc.
- **Lagoon™** is also suitable on melamine, PVC and laminated floors.
- Recommended for frequent cleaning, **Lagoon™** cleans effectively and preserves the original finish of the floor.
- **Lagoon™** is enriched with newly developed detergents, and therefore does not require rinsing, leaving the floor spotless.

N.B: **Lagoon™** should not be used on waxed wood floors.

## SURFACE PREPARATION

- If necessary, remove dust from the floor (vacuum cleaner, broom).

## DIRECTIONS FOR USE

- Shake well before use.
- Spray **Lagoon™** onto a small area and wipe off using a clean, micro-fibre mop or a floor cloth. Always use clean equipment, dampened but not dripping in order not to wet the floor too much.
- Repeat the procedure for the rest of the room.

NB: it is also possible to spray **Lagoon™** on the micro-fibre mop itself. In that case, re-impregnate regularly.

- If necessary, the micro-fibre cloth can be washed in the washing-machine.
- No need to rinse the surface; just allow it to dry.

NB: to restore dull lacquered floors, use Blanchon Protector (for satin or gloss finishes) or Blanchon Metamat® (for matt finishes) on a regular basis. These products are perfectly compatible with **Lagoon™**.

## DRYING TIMES

- Drying time: 5 to 10 minutes.
- Return to use: as soon as the floor is dry.

## COVERAGE RATE

- Around 100 to 200 m<sup>2</sup> with 1/2 litre.

**Blanchon**

## TECHNICAL DATA

USE	Maintenance of wooden floors
RESINS TYPE	Surfactants, polymers Silicone free
AFNOR CLASSIFICATION	N/A
DENSITY	1 (at 20°C, as per NF T 30020)
REGULATORY INFORMATION	Refer to the relevant Material Safety Data Sheets (also available on <a href="http://www.blanchon.com">www.blanchon.com</a> <a href="http://www.quickfds.com">www.quickfds.com</a> )
DRYING TIME	5 to 10 minutes approximately
ABRASION RESISTANCE (TABER)	N/A
IMPACT RESISTANCE	N/A
SCRATCH RESISTANCE	N/A
STORAGE	Protect from frost (be careful of storing in vehicles)

The information provided in this Technical Data Sheet is given in good faith for information purposes only. In no case whatsoever can this information be considered as a guarantee given by us nor engage our responsibility when our products are used. Since we are constantly striving to improve our products, the information given here may be subject to modification without prior notice. This Technical Data Sheet cancels and supersedes all previous versions.

Technical Data Sheet issued on the 10.05.2012.

Respect  
for people and  
the environment



[www.blanchon.com](http://www.blanchon.com)

28 rue Charles Martin - BP 105  
69192 SAINT-FONS CEDEX - FRANCE  
Tél. 04 72 89 06 00 - Fax 04 78 70 07 18  
Export Lines: Tel: (0033) 472 89 06 09  
Fax: (0033) 472 89 06 02

**Blanchon**

BLANCHON S.A. - Est. 1832 - A stock company with a board of directors and a supervisory board, with a registered capital of € 4 258 258  
390 112 886 RCS LYON - APE 2030 Z - E-mail: [info.uk@blanchon.com](mailto:info.uk@blanchon.com)  
Internet : [www.blanchon.com](http://www.blanchon.com)