

Compatible with
all oiled surfaces

Excellent adhesion to
all oiled finishing coats



Dries within 20 minutes



Strong regenerative
properties



Anti-slip coating: anti-
slip properties certified
by NF EN 13036-4



Easy application with
a spray bottle



No polishing



Odourless



Universal Maintenance Oil



INTENDED USE AND PRODUCT RANGE

- The true technical innovation, the **Universal Maintenance Oil** protects and regenerates all oiled parquets (oiled either by the producer or end-user), suitable for traditional finishing coats or coats in the water-based phase*.
- Simple and practical to use, the **Universal Maintenance Oil** is applied directly onto clean wood: it does not require hand polishing or by using a buffing machine. The preparation in a spray bottle can be sprayed directly onto the surface.
- Its quick drying, odourless formula and ease of application make the rooms ready to use almost immediately: after 20 minutes.
- The **Universal Maintenance Oil** revives greyish parquets by maintaining their original appearance.
- It does not leave a slippery coat: anti-slip properties certified by NF EN 13036-4 (the protocol is available upon request).
- Available in 0.5 L spray bottle and 1 L can.

*Perform a test for adhesion beforehand.

SURFACE PREPARATION

- **Universal Maintenance Oil** is meant for parquets and floors impregnated with all types of Blanchon oils: Hard Waxoil, Wood Floor Oil, Solid'oil™, Original Wood™ Environment Maintenance Oil. At the same time, it is ideal for floors oiled by the producer.
- **Universal Maintenance Oil** is applied on clean and dry surfaces.
- Thoroughly clean the surface from dust with a broom or vacuum cleaner.
- For regular cleaning and degreasing, use Blanchon Soap For Oiled Surfaces, and for everyday washing use the Blanchon Lagoon® preparation (apply with properly wrung out, non-dripping tools); to remove stubborn stains or dirt and thoroughly clean the surface, use Blanchon Powerful Cleaner.
- Remove the minor scratches, visible on the surface with fine sandpaper.

IMPORTANT:

- First cleaning should be performed only after 7 to 10 days, after thorough drying of the finishing coat.
- If the surface shows signs of significant wear (scratches reaching raw wood), it is recommended to re-impregnate it with the original oil in order to avoid differences in colour.

INSTRUCTIONS FOR USE

- **Universal Maintenance Oil** should be used when the floor impregnated with original oil loses its natural gloss (show signs of normal wear and tear, there are small cracks, etc.).
- A ready for use preparation: do not dilute, shake well before and during use. Do not perform parquet maintenance at temperatures below 12°C.
- Apply a thin layer of the **Universal Maintenance Oil** with a microfibre mop on a clean and dry floor covered with oil. The possibility of using a product in a spray bottle: spray the preparation directly onto the surface, then wipe with a microfibre cloth immediately.
- The oil sets quickly, so its prolonged application to the surface is unnecessary. Using a polisher or a rotary machine is completely needless and not recommended.
- The surface dries in about 15-20 minutes. The room can be used after this time.
- When the floor is subjected to intensive use, regular maintenance can be supplemented with applying a fresh coat of the original oil (see point CARING AND RENOVATION on the next page).

WELL CARED PARQUETS COVERED WITH OIL GROW BEAUTIFUL OVER TIME.

Blanchon

Universal Maintenance Oil

Cleaning of tools

- Rinse thoroughly with water immediately after use.
- Protect the environment:
 - Wring the tools properly and wipe them dry immediately after use.
 - Wash them in a dish with a small amount of water. Leave the used water to evaporate.
 - The accumulated dry sediments can be disposed of with trash.
 - Tightly close the container after use.
 - Return the empty container for recycling.
 - Please contact the local authorities for information on the collection and disposal of wastes.
 - Do not pour liquid wastes into sewer systems.

DRYING AND USE

- Dust-dry: about 10 minutes.
- Moderate use of room: after 20 minutes under standard conditions. Use caution within the first hour.
- Place adequate covers (made of felt) under chair and table legs. If necessary, place a doormat at the entrance to the room, which will keep dust and gravel from spreading. Do not allow any water or other liquid spillages on the oiled surface (secure the flowerpots well). Do not move heavy furniture. Clean with a vacuum cleaner or broom (do not use damp cloths).

PERFORMANCE

- 40 m² from 1 L with one layer.
- 20/25 m² from 0.5 L spray bottle.

STORAGE

- Protect against frost (use caution when storing in vehicles).
- Rinse the spray nozzle thoroughly with clean water after each use to avoid clogging.

CARING AND RENOVATION

- **Regular cleaning:** wet wiping with Soap For Oiled Surfaces diluted in a proportion of 50 ml per 5 litres of water, with tools properly wrung out from water excess.
- **Intensive cleaning:** wet wiping with Powerful Cleaner diluted in a proportion of 100 ml per 5 litres of warm water in the case of surfaces covered with oil in the aqueous phase or 200 ml per 5 litres of warm water in the case of conventional oil. Wash the surface with clean water, with a tool properly wrung out from water excess.
- **Regular care:** apply **Universal Maintenance Oil** on a clean and dry floor covered with oil using a microfibre mop.
- **Limited renovation:** applied in the case of particularly damaged areas (visible raw wood, impact marks, cracks...), grind the damaged areas vigorously (with fine sandpaper) and re-impregnate them with the original oil (apply a thin layer with a clean, soft cotton cloth). Do not use steel wool. In order to supplement the perfect appearance, follow the instructions described in point Regular care.
- **General renovation:** matt the entire surface with a rotary machine equipped with an abrasive mesh (gradation of 120-150), vacuum it, and then apply a thin layer of the original oil.

TECHNICAL DATA

| | |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| INTENDED USE | Universal Maintenance Oil for all oiled floors |
| RESIN TYPE | Oils in the aqueous phase |
| AFNOR CLASSIFICATION | Group 1, Class 7B2 |
| DENSITY | 1.01 (at temp. 20°, according to NF T 30020) |
| ADDITIONAL INFORMATION | Refer to the appropriate Material Safety Data |
| RESISTANCE TO CHEMICAL PRODUCTS | Perfect in terms of: vegetable oil, mustard, ketchup, vinegar, water, coffee, tea, household detergents, 40% alcohol, ink, diluted bleach (after 20 days of drying, according to NF T 30053) |

The Technical Data Sheet has been approved by the Technical Department and published on 05.2015.
The product has been developed and manufactured in France.
All the tips and recommendations contained in this data sheet are given in good faith for informational purposes.
The company cannot be held responsible for any losses incurred as a result of improper or incorrect use of its materials.
This Technical Data Sheet replaces the previous versions and contains updated information on the product

28 rue Charles Martin - BP 105
69192 SAINT-FONS CEDEX - FRANCE Tél. 04 72 89 06 00 - Fax 04
78 70 07 18
Export Lines: Tel: (0033) 472 89 06 09
Fax: (0033) 472 89 06 02

Blanchon

BLANCHON S.A. - Est. 1832 - A stock company with a board of directors and a supervisory board,
with a registered capital of 4 258 258
390 112 886 RCS LYON - APE 2030 Z - E-mail: info.uk@blanchon.com
Internet : www.blanchon.com